

Product designation**Pulso 8 lamp**

Article no. 32.118.XX

Product description

Lamp with sturdy Noryl housing shell, bayonet mount with automatic lock for interchangeable reflectors and softboxes. Plug-in flash tube 6400 J / 5900 K with integrated protecting glass 5500 K. Switch and fuse for modelling light. Integrated tilt mechanism for continuous tilting, for stand or suspension mounting, holder for umbrella bracket. The Pulso 8 lamp is only designed for mains voltage 200 – 240 V.

Scope of delivery

Lamp equipped with flash tube 6400 J / 5900 K, integrated protecting glass 5500 K and halogen modelling lamp.

Protection cap, cable 7.5 m / 24.6 ft, bag with safety bolt for suspended mounting.

Technical data

Flash energy	max. 6400 J
Halogen modelling light	650 W 230 / 240 V
Length of cable	7.5 m / 24.6 ft
Dimensions	120 x 310 x 200 mm / 4.7 x 12.2 x 7.9 inch
Cooling	fan
Weight incl. cable	3.35 kg / 7.4 lb
Stand adapter	for bolts broncolor 12 mm / 0.5 inch, 3/8" thread and bolts Manfrotto 16 mm / 0.6 inch

Compatibility

Power packs Pulso 8, 606, 606 Servor, Grafit*, Pulso*, Opus*, Primo*, Topas*, Nano*

* On these power packs, the lamp Pulso 8 produces a flash time some 50 % longer than the lamps Pulso 2, 4, F2, F4 and G.

Accessories

Flash tube 6400 J / 5900 K
with integrated protecting glass 5500 K art. no. 34.328.00

Halogen modelling lamp 650 W / 220-240 V with fuse art. no. 34.226.XX

All area lights (excl. Mini-HazyLight), P65 (standard), P50, P70, conical snoot, umbrellas.

Special features

- Flash tube 6400 J / 5900 K with integrated protecting glass 5500 K.
- If the Pulso 8 lamp is operated with a Nano 2 respectively Nano A4, the concerned power pack must not be used below power level 8. If used below this power level there is the risk of failure of the flash release and afterglow of the flash tubes.

Application

Very large studios, where a big light output is required (for example furniture or automobile photography).

Arguments

Pulso 8 lamp is convenient to handle and operate (fast replacement of reflectors), resistance against fractures, excellent quality of cable reduces loss of energy by a special bush, non-buckling cable in lamp section and plug, long service life of halogen as a result of cooling even for long flash series, plug identification (power pack identifies lamp via plug coding), mechanical protection of flash tube.