Balloon Data sheet E22

Product designation

Balloon Article no. 33.161.00

Product description

Special area light as accessory to Unilite, Pulso and Primo lamps and the entire range of broncolor monolights.

UV resistant acrylic glass sphere, opal, diameter 50 cm / 19.6" with black plastic socket and Pulso bayonet.

Scope of delivery

Acrylic glass sphere with plastic socket and Pulso bayonet.

Technical data

Diameter 50 cm / 19.6 "

Number of flashes With a cooled down Balloon a continuous series of:

maximum 100 flashes (flash output 3200 J / halogen

modelling light 300 W) or

maximum 50 flashes (flash output 3200 J / halogen

modelling light 650 W) is permitted

Compatibility

Lamps Unilite, Pulso and Primo lamp bases

Monolights Minipuls, Compuls, Minipuls C, Minipuls D, Minicom

Application

The area light with a 360° light angle is ideal for shooting interiors, and portrait photography. Due to the characteristic of the light, unconventional light control is also possible.

Special features

To prevent overheating additional lamps must be located at a minimum distance of 1 meter away from the acrylic glass sphere. A cooling-off period of approx. 30 minutes must be observed after a continuous series of maximum 100 respectively 50 flashes.

A warm Balloon must never be put down on its acrylic glass sphere, only on its socket.