

Product designation

Boxlite 40

Article no. 32.341.XX

Product description

Small panel light in the dimensions 30 x 40 cm (12" x 16")

Plexiglass diffuser, plexiglass housing

Steel sheet rear wall with cable port and holder with bracket and quick change head and 5 m (16 ft.) cable

Boxlite 40 with 2 flash tubes, 4 modelling lamps 4 x 40 W

Scope of delivery

Boxlite with cable, bracket holder and quick change head

Technical data

Dimensions (without quick change head)

30 x 40 x 15 cm (12" x 16" x 6")

Format light area

30 x 40 cm (12" x 16")

Flash energy

max. 1600 J

Number of flashes

to protect against overheating, a cooling-off period of approx. 20 minutes must be observed after a maximum of 40 flashes 1600 J

F-stop at 2 m (6 ½ ft)
1600 J, 100 ISO

22 3/10

Modelling light switch

switch on the rear wall of the housing

Compatibility

Power packs

Grafit 2, 4, A2, A4, A2 RFS, A4 RFS, A8 RFS, A2 plus, A4 plus, Topas A2, A4, A8
Nano 2, Mobil, Mobil A2R
Primo, Primo A, Primo A fashion, Primo 4,
Pulso 2, A2, 4, A4, Pulso G
Opus 2, A2, A4, A8

Special features

Proportionality modelling light/flash light with the remaining lights of the product line cannot be implemented for thermal reasons.

Application

This light was primarily designed for the section objects shots and small object photography. Boxlite is ideally suited as a light source for slide duplication.