

Product designation**Striplite 120 Evolution**

Article no. 32.303.XX

Product description

Light with dimensions 112 x 12 cm / 44 x 4.7 inches, can be operated at up to 2 x 3200 J, plexiglass diffuser, sheet steel back with cable outlet, 5 meter / 16.4 ft. cable, modelling light switch, and separate interchangeable tilt head.

Scope of delivery

Striplite with two cables, flash tubes, modelling lamps and interchangeable tilt head.

Technical data

Flash energy		2 x 3200 J
F-stop at 2 m (6 ½ ft.), 100 ISO		45
Modelling light	220 V	20 x 20 W / 24 V
	110 V	20 x 20 W / 12 V
Cable length		2 x 5 m (16.4 ft.)
Cooling		2 fans
Dimensions		112 x 12 x 13 cm / 44 x 4.7 x 5.1 inches
Weight		6.8 kg / 15 lb

Compatibility

Power packs	Grafit 2, 4, A2, A4, A2 RFS, A8 RFS, A2 plus, A4 plus, Topas A2, A4, A8 Nano 2, Mobil, Mobil A2R Primo, Primo A, Primo A fashion, Primo 4 Pulso 2, A2, 4, A4, Opus 2, A2, 4, A4, A8,
-------------	---

For heat-related reasons, it is not possible to equip the Striplite with a proportional halogen modelling lamp matching the other lamps.

Accessories

- Art. no. 33.218.00 Honeycomb grid to Striplite 120
- Art. no. 33.229.00 Barn door to Lightbar/Striplite 120
- Art. no. 33.271.00 Plexi cap transparent to Lightbar 120
- Art. no. 33.273.00 Plexi cap mat to Lightbar 120

Application / arguments

Mirror projection of lines, sharp edges and contours - Separation of the dark background from shiny and not shiny objects - Background gradations - The slim built product allows a precise light control - The possibility of transforming a Striplite into a Lightbar increases the application range - Simple and versatile mounting with the interchangeable tilt head.